



Typical Inspection Data:

Density @ 20 °C	0.849 g/cm ³
Viscosity @ 100 °C	11.8 cSt
Viscosity @ 40 °C	68 cSt
Viscosity Index	171
Viscosity CCS @ -30 °C	6200 cP
T.B.N.	6.6 mg KOH/g
Sulphated Ash Mass	0.49%
Zinc	0.10%
Calcium	0.10%
Phosphorus	0.07%
Colour	Brown
Flash Point	230 °C
Pour Point	-39 °C

Specifications:

ACEA C4

Renault RN 0720; MB 226.51

VAUXHALL TRADE CLUB

C4 5W-30

Fully Synthetic Low SAPS Engine Oil

Description:

Vauxhall Trade Club C4 5W-30 is a fully synthetic multigrade engine oil designed for use in light duty diesel and petrol engines found in many passenger cars and vans.

It is formulated with premium fully synthetic base stocks and performance additives which enable it to cope with the demanding conditions found in modern engines.

Vauxhall Trade Club C4 5W-30 is designed for use in vehicles fitted with exhaust after treatment systems where its low SAPS (sulphated ash, phosphorus and sulphur) levels ensure the correct operation of devices such as diesel particulate filters and catalytic converters.

Features & Benefits:

- Compatible with after treatment devices
- Long drain intervals
- Excellent thermal stability
- Provides high levels of engine cleanliness

Application:

Vauxhall Trade Club C4 5W-30 is recommended primarily for diesel engines found in certain modern passenger cars and vans produced by Renault, Nissan and Infiniti. It can be used where any of the following specifications and a SAE 5W-30 viscosity grade is required.

Health & Safety:

Please refer to the relevant health and safety data sheet. Copies are available to Trade Club members at www.tradeclub.co.uk

Part Numbers/ Pack Sizes:

- 199L – UKTOBA11
- 20L – UKTOTW11
- 5L – UKTOFL11

Created: 19/07/18

Updated: 16 January 2019 11:15 am

